

MATERIAL SAFETY DATA SHEET

CHEMCO INDUSTRIES, INC.
5731 Manchester Ave., St. Louis, MO 63110



DATE OF ISSUE: January, 05, 2006

GENERAL INFORMATION # : 314-647-1888
EMERGENCY TELEPHONE # : (800) 854-4236

I-PRODUCT IDENTIFICATION

DYNA-SOL

PRODUCT CODE: #086, #086A

CHEMICAL FORMULATION:

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 3 FLAMMABILITY: 1 REACTIVITY: 0
HAZARD RATING: 4- Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - HAZARDOUS INGREDIENTS

Hazardous Components (Specific Chemical Identity; Common Name (s))	CAS No.	OSHA PEL	ACGIH TLV	WEIGHT %
1,1,1, TRICHLOROETHANE*	71-55-6	350ppm	350pm	90-100%
CARBON DIOXIDE	124-38-9	5000ppm	5000ppm	

*Sara 313 Information:

Subject to the reporting and supplier notification of SARA 313.

* RQ #1 1000 LBS

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling Level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III/ List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III/ List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - PHYSICAL DATA

BOILING POINT (°f): N/A MELTING POINT: N/A
VAPOR PRESSURE (psig@25C): 75psig SPECIFIC GRAVITY (H20=1): 1.30
VAPOR DENSITY (AIR=1) >1
SOLUBILITY IN WATER: INSOLUBLE EVAPORATION RATE (Butyl Acetate=1): >1
pH(@25C): N/A
APPEARANCE AND ODOR: WATER WHITE-SWEET ETHERAL ODOR

IV - FIRE AND EXPLOSION HAZARD

FLASH POINT (Method used): NONE (TEST METHOD):
FLAMMABLE LIMITS: N/E UPPER: N/A LOWER: N/A
FLAME PROJECTION: NONE
EXTINGUISHING MEDIA: CO2, STANDARD FOAM, DRY CHEMICAL, HALON
SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS
UNUSUAL FIRE AND EXPLOSION HAZARD: EXPOSURE TO TEMPERATURES OVER 120 DEGREES F MAY CAUSE BURSTING OR VENTING. HEAT OR FIRE MAY CAUSE HAZARDOUS FUMES: CARBON MONOXIDE, PHOSGENE

V - REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY: OXIDIZING MATERIALS
CONDITIONS TO AVOID: AVOID OXIDIZING MATERIALS
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: OPEN FLAMES MAY CAUSE CARBON MONOXIDE
PHOSGENE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: SOURCES OF HEAT

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DYNA-SOL

PRODUCT CODE: #086, #086A

VI - HEALTH AND HAZARD DATA

GENERAL: TOXICITY INFORMATION IS NOT AVAILABLE FOR THESE FINISHED PRODUCTS. THIS HEALTH HAZARD ASSESSMENT IS BASED ON INFORMATION AVAILABLE FOR THE COMPONENTS IN THE FINISHED PRODUCT.

THRESHOLD LIMIT VALUE: N/E

OSHA & ACGIH: N/E

CARCINOGEN - NTP & IARC PROGRAM: NOT CONSIDERED A CARCINOGEN

SYMPTOMS OF EXPOSURE

EYES: MAY CAUSE IRRITATION, REDNESS, OR WATERING

SKIN: MAY CAUSE ITCHING, DRYNESS, REDNESS, OR IRRITATION

INGESTION: NAUSEA, HEADACHE, VOMITING

INHALATION: LARGE AMOUNTS OF VAPORS MAY CAUSE NAUSEA, OR DIZZINESS

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: SKIN SENSITIVITY, CHEMICAL ALLERGIES

PRIMARY ROUTE(S) OF ENTRY: EYES, SKIN, INGESTION, INHALATION

EMERGENCY FIRST AID

IF IN EYES: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION

IF ON SKIN: WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION

IF INGESTED: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION

IF INHALED: REMOVE TO FRESH AIR.

VII - SPILL AND LEAK PROTECTION

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION. DIKE AREA IF POSSIBLE FOR MATERIAL RECOVERY. SMALL QUANTITIES MAY BE ABSORBED WITH ABSORBENT MATERIALS

WASTE DISPOSAL METHOD: DISPOSE OF IN A MANNER APPROVED BY LOCAL, STATE AND FEDERAL REGULATIONS AS WELL AS EPA STANDARDS.

VIII - SPECIAL PROTECTION INFORMATION

VENTILATION: GENERAL VENTILATION RECOMMENDED TO MAINTAIN THE LEVEL OF THE HAZARDOUS INGREDIENTS TO LESS THAN HALF OF THE TLV.

RESPIRATORY PROTECTION: NOT REQUIRED

PROTECTIVE GLOVES: RUBBER GLOVES. FOR SHORT USAGE NONE REQUIRED

EYE PROTECTION: SAFETY GOGGLES. FOR SHORT USAGE NONE REQUIRED

OTHER PROTECTIVE EQUIPMENT: NONE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: DO NOT STORE WHERE TEMPERATURES EXCEED 120 DEGREES FAHRENHEIT.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN

WORK/HYGIENIC PRACTICES: NONE

REVISION DATE: January 05, 2005

Prepared By:

DATE OF ISSUE: January 05, 2005

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Chemco Industries assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.